Appl. No.

10/692,141

Filed

: October 23, 2003

I. <u>AMENDMENTS TO THE CLAIMS</u>

:

The following listing of the claims replaces all prior versions and listing of the claims in the application:

1-17. (Cancelled)

Please cancel Claims 18-26.

27. (Currently Amended) A table comprising:

a table top constructed from blow-molded plastic, the table top including a first side, a second side, a first end, a second end, an upper portion, a lower portion and a hollow interior portion formed during the blow-molding process;

a first leg assembly connected proximate the first end of the table top, the first leg assembly movable between an extended position and a collapsed position relative to the table top;

a second leg assembly connected proximate the second end of the table top, the second leg assembly movable between an extended position and a collapsed position relative to the table top;

a support assembly disposed between the first leg assembly and the second leg assembly, the support assembly disposed between the first side and the second side of the table top, the support assembly comprising:

a first mounting structure integrally formed in the lower portion of the table top during the blow-molding process as part of a unitary structure, the first

Appl. No.

10/692,141

Filed

: October 23, 2003

mounting member including an inner surface and an outer surface;

a first support member connected to the inner surface of the first mounting structure, the first support member being disposed generally parallel to the first

side of the table top;

a second mounting structure integrally formed in the lower portion of the

table top during the blow-molding process as part of a unitary structure, the

second mounting member including an inner surface and an outer surface;

a second support member connected to the inner surface of the second

mounting structure, the second support member being disposed generally parallel

to the second side of the table top, the first support member being disposed

generally parallel to the second support member; and

a crossbar connected to the first support member and the second support

member, the cross bar being disposed generally parallel to the first end and the

second end of the table top; and

a recessed portion integrally formed in the outer surface of the first mounting

structure during the blow-molding process as part of a unitary structure, the recessed

portion extending through a side wall of the first mounting structure and being disposed

generally parallel to the lower portion of the table top, the recessed portion being sized

and configured to form at least a portion of a handle.

28. (Previously Presented) The table as in Claim 27, further comprising a second

cross bar connected to the first support member and the second support member, the second

-3-

Appl. No.

10/692,141

Filed

: October 23, 2003

cross bar being disposed generally parallel to the second end of the table top, the first cross bar being disposed generally parallel to the second cross bar.

29. (Previously Presented) The table as in Claim 27, wherein the first mounting structure has a generally C-shaped configuration with a first end, a second end and an elongated body;

wherein the second mounting structure has a generally C-shaped configuration with a first end, a second end and an elongated body; and

wherein the first mounting structure is spaced apart from and faces the second mounting structure.

30. (Previously Presented) The table as in Claim 29, wherein the first end of the first mounting structure is generally aligned with and spaced apart from the first end of the second mounting structure; and

wherein the second end of the first mounting structure is generally aligned with and spaced apart from the second end of the second mounting structure.

Please cancel Claim 31.

Appl. No.

: 10/692,141

Filed

: October 23, 2003

32. (Currently Amended) A table comprising:

a table top constructed from blow-molded plastic, the table top including a first

side, a second side, a first end, a second end, an upper portion, a lower portion and a

hollow interior portion formed during the blow-molding process;

a first leg assembly connected proximate the first end of the table top, the first leg

assembly movable between an extended position and a collapsed position relative to the

table top;

a second leg assembly connected proximate the second end of the table top, the

second leg assembly movable between an extended position and a collapsed position

relative to the table top;

a support assembly disposed between the first leg assembly and the second leg

assembly, the support assembly disposed between the first side and the second side of the

table top, the support assembly comprising:

a first mounting structure integrally formed in the lower portion of the

table top during the blow-molding process as part of a unitary structure, the first

mounting member including an inner surface and an outer surface;

a first support member connected to the inner surface of the first mounting

structure, the first support member being disposed generally parallel to the first

side of the table top;

a second mounting structure integrally formed in the lower portion of the

table top during the blow-molding process as part of a unitary structure, the

second mounting member including an inner surface and an outer surface;

-5-

Appl. No.

10/692,141

Filed

: October 23, 2003

a second support member connected to the inner surface of the second mounting structure, the second support member being disposed generally parallel to the second side of the table top, the first support member being disposed generally parallel to the second support member; and

a crossbar connected to the first support member and the second support member, the cross bar being disposed generally parallel to the first end and the second end of the table top; and

a recessed portion integrally formed in the lower surface of the table top during the blow-molding process as part of a unitary structure, the recessed portion being disposed between the first mounting structure and the table top, proximate the first mounting structure, the recessed portion being sized and configured to form at least a portion of a handle.

33. (Previously Presented) The table as in Claim 32, further comprising a second cross bar connected to the first support member and the second support member, the second cross bar being disposed generally parallel to the second end of the table top, the first cross bar being disposed generally parallel to the second cross bar.

Appl. No. :

10/692,141

Filed

October 23, 2003

34. (Previously Presented) The table as in Claim 32, wherein the first mounting structure has a generally C-shaped configuration with a first end, a second end and an elongated body;

wherein the second mounting structure has a generally C-shaped configuration with a first end, a second end and an elongated body; and

wherein the first mounting structure is spaced apart from and faces the second mounting structure.

35. (Previously Presented) The table as in Claim 32, wherein the first end of the first mounting structure is generally aligned with and spaced apart from the first end of the second mounting structure; and

wherein the second end of the first mounting structure is generally aligned with and spaced apart from the second end of the second mounting structure.

Please cancel Claim 36.